



Key features

- Access layer switch
- Enterprise-class features
- Layer 2 and Layer 3 lite feature set
- Scalable 10/100/1000 connectivity
- Gigabit fiber uplinks

Datasheet

HP ProCurve Switch 2800 Series

The HP ProCurve Switch 2800 Series consists of two switches: the 24-port HP ProCurve Switch 2824 with 20 10/100/1000 ports, and the 48-port HP ProCurve Switch 2848 with 44 10/100/1000 ports. In addition, each switch has four dual-personality ports for RJ-45 10/100/1000 or mini-GBIC connectivity. The 2800 series is ideal for secure 10/100/1000 connectivity, and it offers access security and advanced prioritization and traffic-monitoring capabilities. With support for IP static routing, the 2800 series is well-suited for environments that need basic routing at the edge of the network.

HP ProCurve Switch 2800 Series

Features and benefits

Industry-leading warranty



Connectivity

- **Dual-personality functionality:** four 10/100/1000 ports or mini-GBIC slots for optional fiber connectivity such as Gigabit-SX, -LX, or -LH

Performance

- **48 Gbps backplane with up to 34.7 million pps (HP ProCurve Switch 2824) and 96 Gbps backplane with up to 69.8 million pps (HP ProCurve Switch 2848):** ten times the bandwidth for low-latency throughput

Resiliency and high availability

- **IEEE 802.3ad Link Aggregation Protocol (LACP) and ProCurve trunking:** support up to 24 trunks, each with up to 8 links (ports) per trunk
- **Spanning Tree Protocol (IEEE 802.1D):** provides redundant links while preventing network loops
- **IEEE 802.1w Rapid Convergence Spanning Tree Protocol:** increases network uptime through faster recovery from failed links
- **IEEE 802.1s Multiple Spanning Tree:** provides high link availability in multiple VLAN environments by allowing multiple spanning trees
- **Optional external redundant power supply:** provides uninterrupted power

Layer 2 switching

- **VLAN support and tagging:** supports the IEEE 802.1Q (4,094 VLAN IDs) and 256 VLANs simultaneously
- **GARP VLAN Registration Protocol:** allows automatic learning and dynamic assignment of VLANs
- **Jumbo packet support:** supports up to 9,216 byte frame size to improve performance of large data transfers

Layer 3 routing

- **Basic IP routing:** enables automatic routing to the connected VLANs and up to 16 static routes—including one default route—in IP networks

Security

- **Dynamic ARP protection:** blocks ARP broadcasts from unauthorized hosts, preventing eavesdropping or theft of network data
- **Dynamic IP lockdown:** works with DHCP protection to block traffic from unauthorized hosts, preventing IP source address spoofing
- **Port security:** allows access only to specified MAC addresses, which can be learned or specified by the administrator
- **MAC address lockout:** prevents configured particular MAC addresses from connecting to the network
- **Multiple user authentication methods:**
 - **IEEE 802.1X:** industry-standard method of user authentication using an IEEE 802.1X supplicant on the client in conjunction with a RADIUS server
 - **Web-based authentication:** similar to IEEE 802.1X, provides a browser-based environment to authenticate clients that do not support the IEEE 802.1X supplicant
 - **MAC-based authentication:** client is authenticated with the RADIUS server based on the client's MAC address
- **Secure FTP:** allows secure file transfer to/from the switch; protects against unwanted file downloads or unauthorized copying of switch configuration file
- **RADIUS/TACACS+:** eases switch management security administration by using a password authentication server
- **Source-port filtering:** allows only specified ports to communicate with each other
- **Secure Shell (SSHv2):** encrypts all transmitted data for secure, remote command-line interface (CLI) access over IP networks
- **Secure Sockets Layer (SSL):** encrypts all HTTP traffic, allowing secure access to the browser-based management GUI in the switch
- **Switch management logon security:** can require either RADIUS or TACACS+ authentication for secure switch CLI logon

♦ For as long as you own the product, with next-business-day advance replacement (available in most countries). The following hardware products and their related series modules have a one-year hardware warranty with extensions available: HP ProCurve Routing Switch 9300m Series, HP ProCurve Switch 8100fl Series, and HP ProCurve Network Access Controller 800. The following hardware mobility products have a one-year hardware warranty with extensions available: HP ProCurve M111 Client Bridge, HP ProCurve MSM3xx-R Access Points, HP ProCurve MSM7xx Mobility and Access Controllers, HP ProCurve RF Manager IDS/IPS Systems, HP ProCurve MSM Power Supplies, HP ProCurve 1-Port Power Injector, and HP ProCurve CNMS Appliances. Disk drives in the HP ProCurve ONE Services z1 Modules have a five-year hardware warranty. Standalone software, upgrades, or licenses may have a different warranty duration. For details, refer to the ProCurve Software License, Warranty, and Support booklet at <http://www.procurve.com/warranty>.

HP ProCurve Switch 2800 Series

Convergence

- **IP multicast snooping and data-driven IGMP:** automatically prevents flooding of IP multicast traffic
- **IEEE 802.1AB Link Layer Discovery Protocol (LLDP):** automated device discovery protocol for easy mapping by network management applications
- **Per-port broadcast throttling:** selectively configures broadcast control on heavy traffic port uplinks

Quality of Service (QoS)

- **Traffic prioritization (IEEE 802.1p):** allows real-time traffic classification into eight priority levels mapped to eight queues
- **Class of Service (CoS):** sets the IEEE 802.1p priority tag based on IP address, IP Type of Service (ToS), L3 protocol, TCP/UDP port number, source port, and DiffServ
- **Layer 4 prioritization:** enables prioritization based on TCP/UDP port numbers

Manageability

- **RMON, XRMON, sFlow, and SMON:** provide advanced monitoring and reporting capabilities for statistics, history, alarms, and events
- **Friendly port names:** allow assignment of descriptive names to ports
- **Auto-MDIX:** automatically adjusts for straight-through or crossover cables on all 10/100/1000 ports
- **Dual flash images:** provides independent primary and secondary operating system files for backup while upgrading
- **Software updates:** free downloads from the Web
- **Stacking capability:** single IP address management for a virtual stack of up to 16 switches, including the HP ProCurve Switch 2500 Series, 2510 Series, 2600 Series, 2800 Series, 2810 Series, 2900 Series, 3400cl Series, 3500yl Series, 4200vl Series, 6108, 6200yl-24G-mGBIC, and 6400cl Series
- **Find-Fix-and-Inform:** finds and fixes common network problems automatically, then informs administrator
- **Troubleshooting:** ingress/egress port monitoring enables network problem-solving
- **Multiple configuration files:** multiple configuration files can be stored to the flash image

Warranty and support

- **ProCurve Lifetime Warranty:** for as long as you own the product, with next-business-day advance replacement (available in most countries).

• **Electronic and telephone support:** limited electronic and telephone support is available from HP. Refer to the HP Web site at www.procurve.com/support for details on the support provided and the period during which support is available.

• **Software releases:** refer to the HP Web site at www.procurve.com/support for details on the software releases provided and the period during which software releases are available.

HP ProCurve Switch 2800 Series

Specifications



HP ProCurve Switch 2824 (J4903A)

HP ProCurve Switch 2848 (J4904A)

Ports		
	20 auto-sensing 10/100/1000 ports (IEEE 802.3 Type 10Base-T, IEEE 802.3u Type 100Base-TX, IEEE 802.3ab Type 1000Base-T); Media Type: Auto-MDIX; Duplex: 10Base-T/100Base-TX: half or full; 1000Base-T: full only	44 auto-sensing 10/100/1000 ports (IEEE 802.3 Type 10Base-T, IEEE 802.3u Type 100Base-TX, IEEE 802.3ab Type 1000Base-T); Media Type: Auto-MDIX; Duplex: 10Base-T/100Base-TX: half or full; 1000Base-T: full only
	1 RS-232C DB-9 console port	1 RS-232C DB-9 console port
	4 dual-personality ports; each port can be used as either an RJ-45 10/100/1000 port or an open mini-GBIC slot (for use with mini-GBIC transceivers)	4 dual-personality ports; each port can be used as either an RJ-45 10/100/1000 port or an open mini-GBIC slot (for use with mini-GBIC transceivers)
Physical characteristics		
Dimensions	14.4(d) x 17.32(w) x 1.75(h) in. (36.58 x 43.99 x 4.45 cm) (1U height)	16.9(d) x 17.32(w) x 1.75(h) in. (42.93 x 43.99 x 4.45 cm) (1U height)
Weight	10.2 lb. (4.63 kg), Fully loaded	10.75 lb. (4.88 kg), Fully loaded
Memory and processor		
Processor	Motorola PowerPC MPC8245 @ 266 MHz, 8 MB flash, 64 MB SDRAM	Motorola PowerPC MPC8245 @ 266 MHz, 8 MB flash, 64 MB SDRAM
Mounting		
	Mounts in an EIA-standard 19 in. telco rack or equipment cabinet (hardware included); horizontal surface mounting only	Mounts in an EIA-standard 19 in. telco rack or equipment cabinet (hardware included); horizontal surface mounting only
Performance		
Latency	< 5.4 μ s (64-byte packets)	< 5.4 μ s (FIFO 64-byte packets)
Throughput	up to 34.65 million pps (64-byte packets)	up to 69.3 million pps (64-byte packets)
Switching capacity	48 Gbps	96 Gbps
MAC address table size	16000 entries	16000 entries
Environment		
Operating temperature	32°F to 131°F (0°C to 55°C)	32°F to 131°F (0°C to 55°C)
Operating relative humidity	15% to 95% @ 104°F (40°C), non-condensing	15% to 95% @ 104°F (40°C), non-condensing
Non-operating/Storage temperature	-40°F to 158°F (-40°C to 70°C)	-40°F to 158°F (-40°C to 70°C)
Non-operating/Storage relative humidity	15% to 95% @ 149°F (65°C), non-condensing	15% to 95% @ 149°F (65°C), non-condensing
Altitude	up to 15000 ft. (4.6 km)	up to 15000 ft. (4.6 km)
Acoustic	Power: < 53 dB; DIN 45635T.19 per ISO 7779 @ < 80°F (25°C)	Power: < 53 dB; DIN 45635T.19 per ISO 7779 @ < 80°F (25°C)
Electrical characteristics		
Maximum heat dissipation	341 BTU/hr (360 kJ/hr)	341 BTU/hr (360 kJ/hr)
Voltage	100-127 / 200-240 VAC	100-127 / 200-240 VAC
Current	0.6 / 0.3 A	0.6 / 0.3 A
Power consumption	100 W	100 W
Frequency	50 / 60 Hz	50 / 60 Hz
Notes	Maximum power rating is the worst-case theoretical maximum power number with fully loaded PoE, 100% traffic, all ports plugged in, and all modules populated.	Maximum power rating is the worst-case theoretical maximum power number with fully loaded PoE, 100% traffic, all ports plugged in, and all modules populated.
Safety		

HP ProCurve Switch 2800 Series

cUL (CSA 950); EN 60950/IEC 60950; NOM-019-SCFI-1994; UL 1950 3rd edition

cUL (CSA 950); EN 60950/IEC 60950; NOM-019-SCFI-1994; UL 1950 3rd edition

Emissions

FCC Class A; VCCI Class A; EN 55022/CISPR 22 Class A

FCC Class A; VCCI Class A; EN 55022/CISPR 22 Class A

Immunity

EN	EN 55024, CISPR 24	EN 55024, CISPR 24
ESD	IEC 61000-4-2; 4 kV CD, 8 kV AD	IEC 61000-4-2; 4 kV CD, 8 kV AD
Radiated	IEC 61000-4-3; 3 V/m	IEC 61000-4-3; 3 V/m
EFT/Burst	IEC 61000-4-4; 1.0 kV (power line), 0.5 kV (signal line)	IEC 61000-4-4; 1.0 kV (power line), 0.5 kV (signal line)
Surge	IEC 61000-4-5; 1 kV/2 kV AC	IEC 61000-4-5; 1 kV/2 kV AC
Conducted	IEC 61000-4-6; 3 V	IEC 61000-4-6; 3 V
Power frequency magnetic field	IEC 61000-4-8; 1 A/m, 50 or 60 Hz	IEC 61000-4-8; 1 A/m, 50 or 60 Hz
Voltage dips and interruptions	IEC 61000-4-11; >95% reduction, 0.5 period; 30% reduction, 25 periods	IEC 61000-4-11; >95% reduction, 0.5 period; 30% reduction, 25 periods
Harmonics	EN 61000-3-2, IEC 61000-3-2	EN 61000-3-2, IEC 61000-3-2
Flicker	EN 61000-3-3, IEC 61000-3-3	EN 61000-3-3, IEC 61000-3-3

Management

HP ProCurve Manager Plus; HP ProCurve Manager (included); command-line interface; Web browser; configuration menu; out-of-band management (serial RS-232C)

HP ProCurve Manager Plus; HP ProCurve Manager (included); command-line interface; Web browser; configuration menu; out-of-band management (serial RS-232C)

Notes

Other mini-GBICs supported: HP ProCurve Gigabit-SX-LC Mini-GBIC (J4858A/B) HP ProCurve Gigabit-LX-LC Mini-GBIC (J4859A/B) HP ProCurve Gigabit-LH-LC Mini-GBIC (J4860A/B)

Other mini-GBICs supported: HP ProCurve Gigabit-SX-LC Mini-GBIC (J4858A/B) HP ProCurve Gigabit-LX-LC Mini-GBIC (J4859A/B) HP ProCurve Gigabit-LH-LC Mini-GBIC (J4860A/B)

Services

3-year, 4-hour onsite, 13x5 coverage for hardware (U2855E)
 3-year, 4-hour onsite, 24x7 coverage for hardware (U2856E)
 3-year, 4-hour onsite, 24x7 coverage for hardware, 24x7 software phone support (U6304E)
 3-year, 24x7 SW phone support, software updates (UE262E)
 Installation with minimum configuration, system-based pricing (U4826E)
 Installation with HP-provided configuration, system-based pricing (U4830E)

3-year, 4-hour onsite, 13x5 coverage for hardware (H4496E)
 3-year, 4-hour onsite, 24x7 coverage for hardware (H2893E)
 3-year, 4-hour onsite, 24x7 coverage for hardware, 24x7 software phone support (U6319E)
 3-year, 24x7 SW phone support, software updates (UE264E)
 Installation with minimum configuration, system-based pricing (U4826E)
 Installation with HP-provided configuration, system-based pricing (U4830E)

Refer to the HP Web site at www.procurve.com/services for details on the service-level descriptions and product numbers. For details about services and response times in your area, please contact your local HP sales office.

Refer to the HP Web site at www.procurve.com/services for details on the service-level descriptions and product numbers. For details about services and response times in your area, please contact your local HP sales office.

Standards and protocols

Device management
 HTML and telnet management

General protocols
 IEEE 802.1D MAC Bridges
 IEEE 802.1p Priority
 IEEE 802.1Q VLANs
 IEEE 802.1w Rapid Reconfiguration of Spanning Tree
 IEEE 802.3ad Link Aggregation Control Protocol (LACP)
 IEEE 802.3x Flow Control
 RFC 768 UDP
 RFC 783 TFTP Protocol (revision 2)
 RFC 792 ICMP
 RFC 793 TCP
 RFC 826 ARP
 RFC 854 TELNET
 RFC 951 BOOTP
 RFC 1542 BOOTP Extensions
 RFC 2030 Simple Network Time

Protocol (SNTP) v4
 RFC 3046 DHCP Relay Agent Information Option

IP multicast
 RFC 3376 IGMPv3

MIBs
 RFC 1213 MIB II
 RFC 1493 Bridge MIB
 RFC 2021 RMONv2 MIB
 RFC 2096 IP Forwarding Table MIB
 RFC 2613 SMON MIB
 RFC 2618 RADIUS Client MIB
 RFC 2620 RADIUS Accounting MIB
 RFC 2665 Ethernet-Like-MIB
 RFC 2668 802.3 MAU MIB
 RFC 2674 802.1p and IEEE 802.1Q Bridge MIB
 RFC 2737 Entity MIB (Version 2)

RFC 2863 The Interfaces Group MIB

Network management
 IEEE 802.1AB Link Layer Discovery Protocol (LLDP)
 RFC 2819 Four groups of RMON: 1 (statistics), 2 (history), 3 (alarm) and 9 (events)
 RFC 3176 sFlow
 SNMPv1/v2c/v3
 XRMON

Security
 IEEE 802.1X Port Based Network Access Control
 RFC 1492 TACACS+
 RFC 2138 RADIUS Authentication
 RFC 2866 RADIUS Accounting
 Secure Sockets Layer (SSL)
 SSHv2 Secure Shell



Network of Choice

HP ProCurve Switch 2800 Series accessories

HP ProCurve 100-FX SFP-LC Transceiver (J9054B)

NEW HP ProCurve 100-BX-D SFP-LC Transceiver (J9099B)

NEW HP ProCurve 100-BX-U SFP-LC Transceiver (J9100B)

HP ProCurve Gigabit-SX-LC Mini-GBIC (J4858C)

HP ProCurve Gigabit-LX-LC Mini-GBIC (J4859C)

HP ProCurve Gigabit-LH-LC Mini-GBIC (J4860C)

NEW HP ProCurve 1000-BX-D SFP-LC Mini-GBIC (J9142B)

NEW HP ProCurve 1000-BX-U SFP-LC Mini-GBIC (J9143B)

HP ProCurve 600 Redundant External Power Supply (J8168A)

HP ProCurve Manager 2.3 (-)

HP ProCurve Network Immunity Manager 1.0 50-device license (J9060A)

HP ProCurve Network Immunity Manager 1.0 +100-device license (J9061A)

HP ProCurve Network Immunity Manager 1.0 unlimited-device license (J9062A)

For more information

To learn more about HP ProCurve Networking, please visit ProCurve.com

© 2008 Hewlett-Packard Development Company, L.P. The information contained herein is subject to change without notice. The only warranties for HP products and services are set forth in the express warranty statements accompanying such products and services. Nothing herein should be construed as constituting an additional warranty. HP shall not be liable for technical or editorial errors or omissions contained herein. January 2009