

## ProCurve Switch 2900 Series

The ProCurve Switch 2900 series consists of two switches: the ProCurve Switch 2900-24G with 24 10/100/1000 ports and the ProCurve Switch 2900-48G with 48 10/100/1000 ports. Both have 4 dual-personality ports for 10/100/1000 or mini-GBIC connectivity. In addition, by including four integrated 10-Gigabit Ethernet ports (two CX4 and two X2), the 2900 series offers the most flexible and easy-to-deploy multiple 10-Gigabit stacking and uplinks in its class. Together with static routing, robust security and management features, free lifetime warranty, and free software updates, the 2900 series is a cost-effective, future-proof solution for customers who are building high-performance networks.



ProCurve Switch  
2900-24G (J9049A)



ProCurve Switch  
2900-48G (J9050A)

# ProCurve Switch 2900 Series

## Features and benefits

### Performance

- **High-performance architecture:** 115 Gbps switching fabric with up to 74 million pps (Switch 2900-24G) and 173 Gbps switching fabric with up to 110 million pps (Switch 2900-48G)

### Connectivity

- **Plug-n-Play 10-Gbps Ethernet for stacking and uplink:** four integrated 10-GbE ports (two CX4 and two X2) built-in on the switch
- **Dual-personality functionality:** four 10/100/1000 ports or mini-GBIC slots for optional fiber connectivity such as Gigabit-SX, -LX, or -LH
- **Stacking capability:** single IP address management for a virtual stack of up to 16 switches, including the ProCurve 2500 series, 2510 series, 2600 series, 2800 series, 2810 series, 2900 series, 3400cl series, 3500yl series, 6108, 6200yl, 6400cl series, 4200vl series, and 4100gl series
- **IPv6 ready:** the switch hardware is capable of supporting IPv6, but IPv6 operation and deployment are not available until enabled via a software update at a later date

- **ProCurve/IEEE Auto-MDIX:** automatically adjusts for straight-through or crossover cables on all 10/100/1000 ports

### Resiliency and high availability

- **IEEE 802.3ad Link Aggregation Protocol (LACP) and ProCurve trunking:** support up to 24 trunks, each with up to 8 links (ports) per trunk
- **IEEE 802.1s Multiple Spanning Tree:** provides high link availability in multiple VLAN environments by allowing multiple spanning trees; provides legacy support for IEEE 802.1d and IEEE 802.1w

### Layer 3 routing

- **Basic IP routing:** enables automatic routing to the connected VLANs and up to 16 static routes--including one default route--in IP networks

### Layer 2 switching

- **VLAN support and tagging:** support complete IEEE 802.1Q (4,096 VLAN IDs) and 256 VLANs

simultaneously

- **GARP VLAN Registration Protocol:** allows automatic learning and dynamic assignment of VLANs
- **Jumbo frames:** on Gigabit and 10-Gigabit ports, allow high-performance remote backup and disaster-recovery services

### Security

- **Port security:** allows access only to specified MAC addresses, which can be learned or specified by the administrator
- **MAC address lockout:** prevents configured particular MAC addresses from connecting to the network
- **Multiple user authentication methods:**
  - **IEEE 802.1X:** industry-standard way of user authentication using an IEEE 802.1X supplicant on the client in conjunction with a RADIUS server
  - **Web-based authentication:** similar to IEEE 802.1X, provides a browser-based environment to authenticate clients that do not support the IEEE 802.1X supplicant
  - **MAC-based authentication:** client is authenticated with the RADIUS server based on the MAC address of the client
- **Authentication flexibility:**
  - **Multiple IEEE 802.1X users per port** provides authentication of up to 8 IEEE 802.1X users per port; prevents user "piggybacking" on another user's IEEE 802.1X authentication
  - **Concurrent IEEE 802.1X and Web or MAC authentication schemes per port** switch port will accept any of IEEE 802.1X and either Web or MAC authentications
- **Source-port filtering:** allows only specified ports to communicate with each other
- **Secure FTP:** allows secure file transfer to/from the switch; protects against unwanted file downloads or unauthorized copying of switch configuration file
- **TACACS+:** eases switch management security administration by using a password authentication

# ProCurve Switch 2900 Series

server

- **Secure Shell (SSHv2):** encrypts all transmitted data for secure, remote command-line interface (CLI) access over IP networks
- **Secure Sockets Layer (SSL):** encrypts all HTTP traffic, allowing secure access to the browser-based management GUI in the switch
- **Switch management logon security:** can require either RADIUS or TACACS+ authentication for secure switch CLI logon
- **Custom banner:** displays security policy when users log in to the switch

## Quality of Service (QoS)

- **Traffic prioritization (IEEE 802.1p):** allows real-time traffic classification into 8 priority levels mapped to 4 queues
- **Class of Service (CoS):** sets IEEE 802.1p priority tag based on IP address, IP Type of Service (ToS), L3 protocol, TCP/UDP port number, source port, and DiffServ
- **Layer 4 prioritization:** enables prioritization based on TCP/UDP port numbers

## Management

- **Port mirroring:** enables traffic on a port to be simultaneously sent to a network analyzer for monitoring
- **sFlow (RFC 3176) :** provides scalable, ASIC-based, wire-speed network monitoring and accounting with no impact on network performance; this allows network operators to gather a variety of sophisticated network statistics and information for capacity planning and real-time network monitoring purposes
- **IEEE 802.1ab LLDP discovery:** advertises and

receives management information from adjacent devices on a network

- **RMON and XRMON:** provide advanced monitoring and reporting capabilities for statistics, history, alarms, and events
- **Friendly port names:** allow assignment of descriptive names to ports
- **Dual flash images:** provide independent primary and secondary OS files for backup while upgrading
- **Find-Fix-and-Inform:** finds and fixes common network problems automatically, then informs administrator

## Convergence

- **IP multicast snooping (data-driven IGMP):** automatically prevents flooding of IP multicast traffic
- **iSCSI support:** enables the deployment of Ethernet storage area network solutions using the iSCSI standard
- **LLDP-MED (Media Endpoint Discovery):** a standard extension of LLDP that stores values for parameters such as QoS and VLAN to automatically configure network devices such as IP phones
- **Software updates:** free downloads from the Web

## Industry-leading warranty

- **Lifetime warranty:** for as long as you own the product, with next-business-day advance replacement (available in most countries)

---

## Services

### ProCurve Switch 2900-24G

- 3-year, 4-hour onsite, 13x5 coverage for hardware (U2855E)

- 3-year, 4-hour onsite, 24x7 coverage for hardware (U2856E)
- 3-year, 4-hour onsite, 24x7 coverage for hardware, 24x7 software phone support (U6304E)
- Installation with minimum configuration,

# ProCurve Switch 2900 Series

system-based pricing (U4826E)

- Installation with HP-provided configuration, system-based pricing (U4830E)

## **ProCurve Switch 2900-48G**

- 3-year, 4-hour onsite, 13x5 coverage for hardware (H4496E)
- 3-year, 4-hour onsite, 24x7 coverage for hardware (H2893E)
- 3-year, 4-hour onsite, 24x7 coverage for hardware, 24x7 software phone support (U6319E)
- Installation with minimum configuration, system-based pricing (U4826E)
- Installation with HP-provided configuration, system-based pricing (U4830E)

# ProCurve Switch 2900 Series



## Specifications

	<b>ProCurve Switch 2900-24G (J9049A)</b>	<b>ProCurve Switch 2900-48G (J9050A)</b>
<b>Ports</b>	20 10/100/1000 ports (IEEE 802.3 Type 10Base-T, IEEE 802.3u Type 100Base-TX, IEEE 802.3ab 1000Base-T Gigabit Ethernet) 2 CX4 10-GbE ports 2 X2 ports 1 RS-232C DB-9 console port 4 dual-personality ports - each port can be used as either an RJ-45 10/100/1000 port (IEEE 802.3 Type 10Base-T; IEEE 802.3u Type 100Base-TX; IEEE 802.3ab 1000Base-T Gigabit Ethernet) or an open mini-GBIC slot (for use with mini-GBIC transceivers)	44 10/100/1000 ports (IEEE 802.3 Type 10Base-T, IEEE 802.3u Type 100Base-TX, IEEE 802.3ab 1000Base-T Gigabit Ethernet) 2 CX4 10-GbE ports 2 X2 ports 1 RS-232C DB-9 console port 4 dual-personality ports - each port can be used as either an RJ-45 10/100/1000 port (IEEE 802.3 Type 10Base-T; IEEE 802.3u Type 100Base-TX; IEEE 802.3ab 1000Base-T Gigabit Ethernet) or an open mini-GBIC slot (for use with mini-GBIC transceivers)
<b>Power supplies</b>		
<b>Physical characteristics</b>		
Dimensions	15.43(d) x 17.44(w) x 1.73(h) in. (39.2 x 44.3 x 4.4 cm) (1U height)	16.93(d) x 17.44(w) x 1.73(h) in. (43.0 x 44.3 x 4.4 cm) (1U height)
Weight	14.11 lb. (6.3 kg)	15.43 lb. (7 kg)
<b>Memory and processor</b>		
Processor type and speed	Freescle PowerPC 8540 @ 667 MHz	Freescle PowerPC 8540 @ 667 MHz
Packet buffer size	13.5 MB	22.5 MB
Flash capacity	4 MB	4 MB
<b>Mounting</b>	Mounts in an EIA-standard 19 in. telco rack or equipment cabinet (hardware included); horizontal surface mounting only.	Mounts in an EIA-standard 19 in. telco rack or equipment cabinet (hardware included); horizontal surface mounting only.
<b>Performance</b>		
Latency	1000 Mb <3.7 μs (FIFO 64-byte packets)	1000 Mb <3.7 μs (FIFO 64-byte packets)
Latency	10 Gbps <2.1 μs (FIFO 64-byte packets)	10 Gbps <2.1 μs (FIFO 64-byte packets)
Throughput	Up to 74 million pps (64-byte packets)	Up to 110 million pps
Routing/switching capacity	101 Gbps	148 Gbps
Switching capacity	115 Gbps	173 Gbps
<b>Environment</b>		
Operating temperature	32°F to 131°F (0°C to 55°C); 32°F to 104°F (40°C) when using any X2 optics or transceiver	32°F to 131°F (0°C to 55°C); 32°F to 104°F (40°C) when using any X2 optics or transceiver
Operating relative humidity	15% to 95% @ 104°F (40°C), non-condensing	15% to 95% @ 104°F (40°C), non-condensing
Non-operating/storage temperature	-40°F to 158°F (-40°C to 70°C)	-40°F to 158°F (-40°C to 70°C)
Non-operating/storage relative humidity	15% to 90% @ 149°F (65°C), non-condensing	15% to 90% @ 149°F (65°C), non-condensing
Altitude	up to 15,091 ft.(4.6 km)	up to 15,091 ft.(4.6 km)
Acoustic	DIN 45635T.19 per ISO 7779 49.3 dB	DIN 45635T.19 per ISO 7779 52 dB
<b>Electrical characteristics</b>		
Description	The switch automatically adjusts to any voltage between 100-127 and 200-240 volts and either 50 or 60 Hz	The switch automatically adjusts to any voltage between 100-127 and 200-240 volts and either 50 or 60 Hz

# ProCurve Switch 2900 Series

Maximum heat dissipation	683 BTU/hr ( 720.57 kJ/hr )	683 BTU/hr ( 720.57 kJ/hr )
Voltage	100-127 VAC/200-240 VAC	100-127 VAC/200-240 VAC
Current	4.0 A/2.0 A	4.0 A/2.0 A
Power consumption	200 W	200 W
Frequency	50/60 Hz	50/60 Hz
<b>Safety</b>	CSA 22.2 No. 60950; UL 60950; IEC60950; EN60950	CSA 22.2 No. 60950; UL 60950; IEC60950; EN60950
<b>Emissions</b>	FCC Class A; EN55022/CISPR-22 Class A; VCCI Class A	FCC Class A; EN55022/CISPR-22 Class A; VCCI Class A
<b>Immunity</b>		
EN	EN55024, CISPR 24	EN55024, CISPR 24
ESD	IEC 61000-4-2; 4kV CD, 8 kV AD	IEC 61000-4-2; 4kV CD, 8 kV AD
Radiated	IEC 61000-4-3; 3V/m	IEC 61000-4-3; 3V/m
EFT/Burst	IEC 61000-4-4; 1.0 kV (power line), 0.5 kV (signal line)	IEC 61000-4-4; 1.0 kV (power line), 0.5 kV (signal line)
Surge	IEC 61000-4-5; 1 kV/2 kV AC	IEC 61000-4-5; 1 kV/2 kV AC
Conducted	IEC 61000-4-6; 3V	IEC 61000-4-6; 3V
Power frequency magnetic field	IEC 61000-4-8; 1A/m, 50 or 60 Hz	IEC 61000-4-8; 1A/m, 50 or 60 Hz
Voltage dips and interruptions	IEC 61000-4-11; >95% reduction, 0.5 period; 30% reduction, 25 periods	IEC 61000-4-11; >95% reduction, 0.5 period; 30% reduction, 25 periods
Harmonics	IEC 61000-3-2; IEC61000-3-2	IEC 61000-3-2; IEC61000-3-2
Flicker	IEC 61000-3-3; IEC61000-3-3	IEC 61000-3-3; IEC61000-3-3
<b>Management</b>	ProCurve Manager Plus; ProCurve Manager (included); command-line interface; Web browser; configuration menu; out-of-band management (serial RS-232C)	ProCurve Manager Plus; ProCurve Manager (included); command-line interface; Web browser; configuration menu; out-of-band management (serial RS-232C)

# ProCurve Switch 2900 Series

## Standards and protocols

RFC 783 TFTP; RFC 951 BootP; RFC 854 Telnet; RFC 768 UDP; RFC 792 ICMP; RFC 793 TCP; RFC 826 ARP; RFC 2030 SNTP; IEEE 802.3x Flow Control; DHCP Relay; RFC 3376 IGMPv1/v2/v3; IEEE 802.1D Spanning Tree; IEEE 802.1w Rapid Convergence Spanning Tree; IEEE 802.1s Multiple Spanning Trees; IEEE 802.3ad Link Aggregation Control Protocol; IEEE 802.1AB Link Layer Discovery Protocol; ANSI/TIA-1057 LLDP Media Endpoint Discovery (MED); RFC 2474 DiffServ Precedence; RFC 2597 DiffServ Expedited Forwarding (EF); RFC 2598 DiffServ Assured Forwarding (AF); RFC 1492 TACACS+; RFC 2138 RADIUS; RFC 2866 RADIUS accounting; SSHv2 Secure Shell; Secure Sockets Layer (SSL); IEEE 802.1X Network Login; IEEE 802.1Q VLAN tagging; IEEE 802.1Q GVRP; IEEE 802.1p Priority; SNMPv1/v2c/v3; HTML and telnet management; RFC 1493 Bridge MIB; RFC 1213 MIB II; RFC 2737 Entity MIB; RFC 2863 Evolution of Interface; RFC 2665 Ethernet MIB; RFC 2819 Four groups of RMON: 1 (statistics), 2 (history), 3 (alarm) and 9 (events); XRMON; sFlow; RFC 2021 RMON probe configuration (RMON v2); RFC 2668 802.3 MAU MIB; RFC 2613 SMON; RFC 2674 802.1p and IEEE 802.1Q Bridge MIB; RFC 2618 RADIUS Client MIB; RFC 2620 RADIUS Accounting MIB; RFC 3046 DHCP Relay Agent Information Option

RFC 783 TFTP; RFC 951 BootP; RFC 854 Telnet; RFC 768 UDP; RFC 792 ICMP; RFC 793 TCP; RFC 826 ARP; RFC 2030 SNTP; IEEE 802.3x Flow Control; DHCP Relay; RFC 3376 IGMPv1/v2/v3; IEEE 802.1D Spanning Tree; IEEE 802.1w Rapid Convergence Spanning Tree; IEEE 802.1s Multiple Spanning Trees; IEEE 802.3ad Link Aggregation Control Protocol; IEEE 802.1AB Link Layer Discovery Protocol; ANSI/TIA-1057 LLDP Media Endpoint Discovery (MED); RFC 2474 DiffServ Precedence; RFC 2597 DiffServ Expedited Forwarding (EF); RFC 2598 DiffServ Assured Forwarding (AF); RFC 1492 TACACS+; RFC 2138 RADIUS; RFC 2866 RADIUS accounting; SSHv2 Secure Shell; Secure Sockets Layer (SSL); IEEE 802.1X Network Login; IEEE 802.1Q VLAN tagging; IEEE 802.1Q GVRP; IEEE 802.1p Priority; SNMPv1/v2c/v3; HTML and telnet management; RFC 1493 Bridge MIB; RFC 1213 MIB II; RFC 2737 Entity MIB; RFC 2863 Evolution of Interface; RFC 2665 Ethernet MIB; RFC 2819 Four groups of RMON: 1 (statistics), 2 (history), 3 (alarm) and 9 (events); XRMON; sFlow; RFC 2021 RMON probe configuration (RMON v2); RFC 2668 802.3 MAU MIB; RFC 2613 SMON; RFC 2674 802.1p and IEEE 802.1Q Bridge MIB; RFC 2618 RADIUS Client MIB; RFC 2620 RADIUS Accounting MIB; RFC 3046 DHCP Relay Agent Information Option

## Notes

One 0.5 m 10-GbE CX4 cable is included. When using mini-GBICs with this product, mini-GBICs with revision "B" (product number ends with the letter "B", e.g. J4858B, J4859B) or later are required. ProCurve 10-GbE CX4 Media Converter (J8439A) can be used only with the two fixed CX4 ports.

One 0.5 m 10-GbE CX4 cable is included. When using mini-GBICs with this product, mini-GBICs with revision "B" (product number ends with the letter "B", e.g. J4858B, J4859B) or later are required. ProCurve 10-GbE CX4 Media Converter (J8439A) can be used only with the two fixed CX4 ports.

# ProCurve Switch 2900 Series

## Accessories



### ProCurve Gigabit-LH-LC Mini-GBIC (J4860B)

with one 1000Base-LH port; designed for long-distance single-mode fiber connectivity

#### Ports

1 1000Base-LH port (no IEEE standard exists for 1550 nm optics)

Duplex: full

Connectors: LC

#### Physical characteristics

Dimensions: 2.167 (d) x 0.604 (w) x 0.463 (h) in. (5.5 x 1.53 x 1.18 cm)

Weight: 0.04 lb. (0.02 kg)

#### Cabling

Low metal content, single-mode fiber-optic, complying with ITU-T G.652 and ISO/IEC 793-2 Type B1

#### Maximum distance

70 km



### ProCurve Gigabit-LX-LC Mini-GBIC (J4859B)

with one 1000Base-LX port; designed for long-distance single-mode fiber connectivity, will support multimode fiber connectivity to limited distances

#### Ports

1 1000Base-LX port (IEEE 802.3z Type 1000Base-LX)

Duplex: full

Connectors: LC

#### Physical characteristics

Dimensions: 2.24 (d) x 0.54 (w) x 0.486 (h) in. (5.69 x 1.37 x 1.23 cm)

Weight: 0.04 lb. (0.02 kg)

#### Cabling

Either single mode or multimode

62.5/125  $\mu\text{m}$  or 50/125  $\mu\text{m}$  (core/cladding) diameter, graded-index, low metal content, multimode fiber optic, complying with ITU-T G.651 and ISO/IEC 793-2 Type A1b or A1a, respectively

Low metal content, single-mode fiber-optic, complying with ITU-T G.652 and ISO/IEC 793-2 Type B1

#### Maximum distance

10 km (single mode) or 550 m (multimode)



### ProCurve Gigabit-SX-LC Mini-GBIC (J4858B)

with one 1000Base-SX port; designed for short-distance (<550 m max.) multimode fiber connectivity

#### Ports

1 1000Base-SX port (IEEE 802.3z Type 1000Base-SX)

Duplex: full

Connectors: LC

#### Physical characteristics

Dimensions: 2.24 (d) x 0.54 (w) x 0.486 (h) in. (5.69 x 1.37 x 1.23 cm)

Weight: 0.04 lb. (0.02 kg)

#### Cabling

62.5/125  $\mu\text{m}$  or 50/125  $\mu\text{m}$  (core/cladding) diameter, graded-index, low metal content, multimode fiber optic, complying with ITU-T G.651 and ISO/IEC 793-2 Type A1b or A1a, respectively

#### Maximum distance

220 m (62.5  $\mu\text{m}$  core diameter, 160 MHz/km bandwidth)

275 m (62.5  $\mu\text{m}$  core diameter, 200 MHz/km bandwidth)

500 m (50  $\mu\text{m}$  core diameter, 400 MHz/km bandwidth)

550 m (50  $\mu\text{m}$  core diameter, 500 MHz/km bandwidth)



# ProCurve Switch 2900 Series



**ProCurve Switch 10-GbE X2-CX4 Transceiver (J8440B)**  
10-Gigabit X2 transceiver that supports a CX4 connector with distance of 15 m

## Ports

Duplex: full  
Connectors: CX4

## Physical characteristics

Dimensions: 3.54 (d) x 1.42 (w) x 0.53 (h) in. (8.99 x 3.61 x 1.35 cm)  
Weight: 0.18 lb. (0.08 kg)

## Environment

Operating temperature: 32°F to 131°F (0°C to 55°C)

Operating relative humidity: 15% to 95%, non-condensing

## Maximum distance

15 m using CX4 cables  
300 m using optical media converters and multimode fiber cable

## Notes

Use CX4 10-GbE cable (0.5-15 m) or ProCurve 10-GbE CX4 Media Converter (J8439A)

---

## ProCurve 10-GbE CX4 Media Converter (J8439A)

Optical media converter for CX4 (10G copper) mmf cable up to 300 m

## Ports

Duplex: full

## Maximum distance

62.5 μm multimode cable @ 150 MHz/km = 1-50 meters

50 μm multimode cable @ 500 MHz/km = 1-100 meters

50 μm multimode cable @ 2000 MHz/km = 1-300 meters



## ProCurve 10-GbE X2-SC ER Optic (J8438A)

Supports the 10G ER standard. Supports single-mode fiber up to 40 km.\*

## Ports

1 10-Gigabit Ethernet port (IEEE 802.3ae Type 10Gbase-ER 1550 nm serial optics)

Duplex: full  
Connectors: SC

## Physical characteristics

Dimensions: 3.48 (d) x 1.42 (w) x .43 (h) in. (8.84 x 3.61 x 1.09 cm)  
Weight: 0.15 lb. (0.07 kg)

## Environment

Operating temperature: 32°F to 104°F (0°C to 40°C)

Operating relative humidity: 15% to 95%, non-condensing

## Cabling

Low metal content, single-mode fiber-optic, complying with ITU-T G.652 and ISO/IEC 793-2 Type B1

## Maximum distance

30 km\*

## Notes

Conditioning patch cord cables are not supported.

\* Maximum distance 40 km using engineered link.

# ProCurve Switch 2900 Series



## ProCurve 10-GbE X2-SC LR Optic (J8437A)

10-Gigabit X2 transceiver that supports LR distance of 10 km with SC connector

### Ports

1 10-Gigabit Ethernet port (IEEE 802.3ae Type 10Gbase-LR 1310 nm serial optics)  
Duplex: full

Connectors: SC

### Physical characteristics

Dimensions: 3.48 (d) x 1.42 (w) x 0.43 (h) in. (8.84 x 3.61 x 1.09 cm)

Weight: 0.16 lb. (0.07 kg)

### Environment

Operating temperature: 32°F to 104°F (0°C to 40°C)

Operating relative humidity: 15% to 95%, non-condensing

### Cabling

Low metal content, single-mode fiber-optic, complying with ITU-T G.652 and ISO/IEC 793-2 Type B1

### Maximum distance

9/125  $\mu$ m single-mode cable = 2 m-10 km

### Notes

Conditioning patch cord cables are not supported.



## ProCurve 10-GbE X2-SC SR Optic (J8436A)

Transceiver that supports 10G SR fiber standard; supports standard 50  $\mu$  and 62.5  $\mu$  mmf up to 300 m

### Ports

1 10-Gigabit Ethernet port (IEEE 802.3ae Type 10Gbase-SR 850 nm serial optics)  
Duplex: full

Connectors: SC

### Physical characteristics

Dimensions: 3.48 (d) x 1.42 (w) x .43 (h) in. (8.84 x 3.61 x 1.09 cm)

Weight: 0.64 lb. (0.29 kg)

### Environment

Operating temperature: 32°F to 104°F (0°C to 40°C)

Operating relative humidity: 15% to 95%, non-condensing

### Maximum distance

62.5  $\mu$ m multimode cable @ 160 MHz/km = 2-26 meters

62.5  $\mu$ m multimode cable @ 200 MHz/km = 2-33 meters

50  $\mu$ m multimode cable @ 400 MHz/km = 2-66 meters


50  $\mu$ m multimode cable @ 500 MHz/km = 2-82 meters

50  $\mu$ m multimode cable @ 2000 MHz/km = 2-300 meters

### Notes

62.5  $\mu$ m (core/cladding) diameter or 50  $\mu$ m, 850 nm, low metal content, multimode fiber-optic, complying with the ITU-T G.652 and ISO/IEC 793-2 Type B1 standards

# ProCurve Switch 2900 Series



## **ProCurve Manager Plus 2.1 100-device limited version (J8778A)**

PCM+ provides advanced device management for 100 ProCurve devices, including integration with OpenView#s Network Node Manager product.

### **System requirements**

Minimum Processor: 2.0 GHz Intel Pentium or equivalent

Recommended Processor: 3.0 GHz Intel Pentium or equivalent

Minimum Memory: 512 MB RAM

Recommended Memory: 1 GB RAM

Minimum Disk Space: 5 GB

Recommended Disk Space: 10 GB

### **Operating system**

Microsoft Windows XP Professional (SP1 or greater), Microsoft Windows 2000 Server (SP4 or later), Microsoft Windows XP (SP1 or greater), Microsoft Windows 2003 Server

### **Browsers**

Microsoft Internet Explorer version 5.0 or later

### **Supported platforms**

HP OpenView Network Node Manager version 6.41 or 7.01 or 7.5

### **Features**

Device auto-discovery  
Topology and mapping

Intuitive Explorer-style interface

Usable troubleshooting data and alerts

Device configuration and management

Customize and execute policies across groups

Enhanced network security features

Multiple device configuration management and archiving

Create and configure VLANs across the network

Traffic monitoring and analysis

Auto-configures traffic monitoring of inter-switch links

Software updates with dual flash image support

Modular design for add-in expansion

E-mail/Pager alerts

SNMP trap forwarding

Granular event data via syslog support

OpenView NNM integration

### **Additional requirements**

Additional processing power may be necessary for extensive traffic monitoring



## **ProCurve Manager Plus 2.1 unlimited license (J9009A)**

PCM+ 2.1 unlimited license provides a PCM+ license that does not limit the number of devices managed (It does NOT require the 100 device license).

### **System requirements**

Minimum Processor: 2.0 GHz Intel Pentium or equivalent

Recommended Processor: 3.0 GHz Intel Pentium or equivalent

Minimum Memory: 512 MB RAM

Recommended Memory: 1 GB RAM

Minimum Disk Space: 5 GB

Recommended Disk Space: 10 GB

### **Operating system**

Microsoft Windows XP Professional, Microsoft Windows XP, Microsoft Windows 2003, Microsoft Windows XP Professional (SP1 or greater)

### **Browsers**

Microsoft Internet Explorer version 5.0 or later

### **Supported platforms**

HP OpenView Network Node Manager version 6.41 or 7.01 or 7.5

### **RADIUS server support**

Microsoft IAS

### **Features**

Device auto-discovery

Topology and mapping

Intuitive Explorer-style interface

Usable troubleshooting data and alerts

Device configuration and management

Customize and execute policies across groups

Enhanced network security features

Multiple device configuration management and archiving

Create and configure VLANs across the network

Traffic monitoring and analysis

Auto-configures traffic monitoring of inter-switch links

Software updates with dual flash image support

Modular design for add-in expansion

E-mail/Pager alerts

SNMP trap forwarding

Granular event data via syslog support

OpenView NNM integration

### **Additional requirements**

Additional processing power may be necessary for extensive traffic monitoring

© 2006 Hewlett-Packard Development Company, L.P. The information contained herein is subject to change without notice. The only warranties for HP products and services are set forth in the express warranty statements accompanying such products and services. Nothing herein should be construed as constituting an additional warranty. HP shall not be liable for technical or editorial errors or omissions contained herein.

10/06/06

To learn more, visit [www.procurve.com](http://www.procurve.com)  
Information is subject to change without notice

